





# PAKISTAN STATE OIL COMPANY LIMITED

## MATERIAL SAFETY DATA SHEET

Furnace Oil

MSDS No. 5

### SECTION 5 – REACTIVITY INFORMATION

<b>Stability</b>	Stable
<b>Conditions to avoid</b>	Sources of ignition. Static discharges. High temperatures.
<b>Incompatible substances</b>	Oxidizers such as peroxides, nitric acid, and perchlorates.
<b>Hazardous decomposition products</b>	H <sub>2</sub> S, SO <sub>2</sub> , Carbon monoxide, nitrogen oxides, and numerous aromatic

### SECTION 6 – HEALTH HAZARD INFORMATION

<b>Route of Entry</b>	<input type="checkbox"/> Eye	<b>Hazardous</b>	<input checked="" type="checkbox"/> Eye
	<input checked="" type="checkbox"/> <b>Skin absorption</b> Furnace oil itself, as well as benzene & naphthalene		<input checked="" type="checkbox"/> <b>Skin</b>
	<input checked="" type="checkbox"/> <b>Inhalation</b>		
	<input checked="" type="checkbox"/> <b>Ingestion</b>		
<b>Acute exposure</b>	Coughing, headache, and giddiness following inhalation. Aspiration into the lungs can cause severe pneumonitis (serious lung irritation), with coughing, gagging, shortness of breath, chest pain, and/or pulmonary edema (swelling). Ingestion may produce nausea, vomiting, and cramping. Kidney effects and systemic edema have been reported after severe exposure. H <sub>2</sub> S is very toxic. At concentrations as low as 1 to 5 ppm, nausea and severe eye irritation may occur. Sense of smell may be impaired at about 20 ppm, with headache and respiratory tract lung irritation. At 250 to 500 ppm, potentially fatal pulmonary edema (fluid in the lungs) may occur. Dizziness, sudden (often fatal) collapse, unconsciousness, and death occur at higher concentrations. Note: Pulmonary edema may be delayed as long as 48 hours after exposure.		
<b>Chronic exposure</b>	Kidney, gastrointestinal, blood, and skin disorders. Headache, nausea, vomiting. Fatigue, and severe nervous and respiratory system symptoms may follow survival of H <sub>2</sub> S poisoning.		
<b>Carcinogenicity</b>	Benzene and certain PAHs are known to be carcinogenic. Exposure to fuel oils during refining is considered "probably carcinogenic to humans". IARC and NTP classify untreated and mildly treated mineral oils as known human carcinogens. ACGIH, EPA, NIOSH, and OSHA have not classified them.	<b>Mutagenicity</b> Not known to be mutagenic <b>Sensitization</b> No <b>Irritancy</b> Skin and respiratory tract <b>Teratogenicity</b> NAv <b>Reproductive toxicity</b> NAv	
<b>Toxicologically synergistic</b>	Other CNS depressants can be expected to produce additive or synergistic effects.		

### SECTION 7 – FIRST AID

<b>Inhalation</b>	Move victim to fresh air. Give artificial respiration if breathing has stopped and if a qualified AR administrator is available. Apply CPR if both pulse and breathing have stopped. Obtain medical attention immediately.
<b>Ingestion</b>	Never give anything by mouth if the person is unconscious, rapidly losing consciousness, or convulsing. If the person is conscious, have them drink 8 to 10 ounces of water or milk to dilute the material in the stomach. <b>Do not</b> induce vomiting. If vomiting occurs spontaneously, have the person lean forward to avoid aspiration. Obtain medical attention immediately.
<b>Eye</b>	If irritation occurs, flush eye with lukewarm, gently flowing fresh water for at least 10 minutes.
<b>Skin</b>	Quickly and gently blot away excess chemical. Gently remove contaminated clothing and shoes under running water. Wash gently and thoroughly with water and non-abrasive soap. Obtain medical assistance.

### SECTION 8 – PRECAUTIONARY MEASURES

**Do not attempt rescue of an H<sub>2</sub>S knockdown victim without the use of proper respiratory protective equipment.**

<b>Personal protective equipment</b>	<b>Gloves</b>	Nitrile, Viton™, Polyvinylchloride, Tychem®BR/LV, or Tychem®TK preferred.
	<b>Eye</b>	Chemical safety goggles or face shield, as a good general safety practice.
	<b>Respirator</b>	NIOSH-approved SCBA or air line respirator with escape cylinder.
	<b>Clothing &amp; footwear</b>	Coveralls to prevent skin contact with product. If clothing or footwear becomes contaminated with product, completely decontaminate it before re-use, or discard it.



# PAKISTAN STATE OIL COMPANY LIMITED

## MATERIAL SAFETY DATA SHEET

**Furnace Oil**

**MSDS No. 5**

<b>Engineering controls</b>	Enclose processes. Use local exhaust ventilation to remove vapour at its site of generation. Handle laboratory samples in a fume hood. Use mechanical ventilation in confined spaces.
<b>Handling</b>	Avoid heating open containers of product so as to minimize vapour production and accumulation. Use non-sparking equipment, explosion-proof ventilation, and intrinsically safe electrical equipment. Ground handling equipment. Have clean emergency eyewash and shower readily available in the work area.
<b>procedures &amp; equipment</b>	Keep unauthorized persons away Eliminate all sources of ignition. Ventilate area. Stop leak if it can be done safely. Prevent entry into sewers, waterways, or confined spaces. Absorb or cover with dry earth, sand or other non-combustible material and use clean, non-sparking tools to transfer to container.
<b>Leak &amp; spill Procedure</b>	Consult local authorities for advice.
<b>Waste</b>	May be stored at ambient temperatures. Containers should be vented and equipped with a flame
<b>Storage</b>	Stable during transport. May be transported hot.
<b>Shipping</b>	

### DISCLAIMER

PSO is only marketing the above material and is not the producer. Information presented herein has been reproduced as available on product manufacturer's leaflet as well as various websites, as a guideline for any person handling or coming in contact with the material and is considered to be dependable, accurate and reliable but is not guaranteed to be so.

Since conditions of use are beyond our control, PSO makes no warranties, expressed or implied, except those contained in its written contract of sale or an acknowledgement. Nothing herein contained should be relied upon as a promise or representation.

PSO assumes no responsibility for injury proximately caused to any person by the material due to non-adherence of safety procedure as stipulated in the data sheet or by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendees/consignees take the risk in the use of the material.

---X---