



BLAZE 4T

Advance Technology for Maximum Power and Extra Mileage



PSO Blaze 4T, an advanced technology motorcycle engine oil designed for high performance. It meets the technical standards for Japanese and European motorcycles equipped with a catalytic converter. Its tri-facet low-friction modern technology protects engine, clutch, and gearbox components, ensuring optimal performance and extending the engine service life.

Benefits

- Outstanding resistance against clutch slippage, protection against engine wear, and gearbox pitting with its Tri-facet additive technology.
- Low friction MA2 additive technology ideally compatible with wet-clutch that facilitates smooth gear shifts.
- Ensures longer engine service life with superior cleanliness for both the engine and piston rings.
- Easy starting at low temperatures and adequate oil film at high temperatures, protects engine components from wear.

Applications

- Ideal for Japanese and European motorcycles that recommend the JASO MA2 specification.
- Specifically formulated for motorcycles equipped with a catalytic converter.

Performance Standard

- API SG/CD
- JASO MA2

Typical Characteristics*

PROPERTIES	METHODS	TYPICAL RESULTS	
		20W-40	20W-50
	SAE		
Density @ 15°C, kg/L	ASTM D-4052	0.8922	0.8947
Kinematic Viscosity @ 100°C, cSt	ASTM D-445	14.7	18.7
Kinematic Viscosity @ 40°C, cSt	ASTM D-445	121.5	166.9
Viscosity Index	ASTM D-2270	124	126
Flash Point (COC), °C	ASTM D-92	224	234
Pour Point, °C	ASTM D-97	-24	-21
Total Base Number, mg KOH/g	ASTM D-2896	5.04	5.44

*These typical characteristics mentioned are based on current mean values.

Based on available information, this product does not contain any component that may produce any significant hazard to health when used for the recommended application. Guidelines for health and safety are available in Material Safety Data Sheet of the product. Dispose of used oil, containers, cartons labels in an environment friendly manner. Do not discharge used oil into drain, soil or water. Advice on application not covered in this leaflet, may be obtained from lubricants.technical@psopk.com