



DIESELUBE HD 50

Diesel Engine Oil

PSO Dieselube HD 50, a high performing and high detergency lubricant specially crafted to meet the strict requirements of diesel engines. It is the ideal choice for engines where API CD/SE oil is recommended.

Benefits

- Ensures effective control of engine wear and deposits on critical engine parts.
- A budget-friendly option with excellent all-around performance.
- Provides reliable protection against rust and corrosion.

Applications

- Ideal for applications that demand the performance level of API classification CD/SE.
- An appropriate choice for a broad range of diesel engine vehicles used in agriculture and off-road applications.
- Suitable for use in both heavy and light commercial vehicles.

Performance Standard

- API CD/SE

Typical Characteristics*

PROPERTIES	METHODS	TYPICAL RESULTS
SAE		50
Density @ 15°C, kg/L	ASTM D-4052	0.9163
Kinematic Viscosity @ 100°C, cSt	ASTM D-445	19.2
Kinematic Viscosity @ 40°C, cSt	ASTM D-445	242.9
Viscosity Index	ASTM D-2270	92
Flash Point (COC), °C	ASTM D-92	244
Pour Point, °C	ASTM D-97	-6
Total Base Number, mg KOH/g	ASTM D-2896	10

*These typical characteristics mentioned are based on current mean values.

Based on available information, this product does not contain any component that may produce any significant hazard to health when used for the recommended application. Guidelines for health and safety are available in Material Safety Data Sheet of the product. Dispose of used oil, containers, cartons labels in an environment friendly manner. Do not discharge used oil into drain, soil or water. Advice on application not covered in this leaflet, may be obtained from lubricants.technical@psopk.com