



CARIENT CNG PLUS

Extra Protection Against High Temperature



PSO Carient CNG Plus is a multi-grade advanced version of CNG Engine Oil. It is formulated to combat high temperature caused by dry combustion in CNG fuel operated engines and ensures excellent engine performance under all climatic conditions. It provides optimum protection against oxidation and gives improved drain interval.

Benefits

- Superior protection of engine parts against high temperatures in CNG vehicles.
- Special antioxidant additive reduces sludge formation and increases oil drain interval.

Application

- Developed for naturally aspirated or turbocharged vehicles operating under moderate to severe working and load conditions.

Performance Standard

- API SL/CF

Typical Characteristics*

PROPERTIES	METHODS	TYPICAL RESULTS
		20W-50
Density @ 15°C, kg/L	ASTM D-4052	0.8967
K. Viscosity @ 100°C, cSt	ASTM D-445	19.78
K. Viscosity @ 40°C, cSt	ASTM D-445	178.50
Viscosity Index	ASTM D-2270	128
Flash Point (COC), °C	ASTM D-92	230
Pour Point, °C	ASTM D-97	-21
Total Base Number, mg KOH/g	ASTM D-2896	8

*These typical characteristics mentioned are based on current mean values.

Based on available information, this product does not contain any component that may produce any significant hazard to health when used for the recommended application. Guidelines for health and safety are available in Material Safety Data Sheet of the product. Dispose of used oil, containers, cartons labels in an environment friendly manner. Do not discharge used oil into drain, soil or water. Advice on application not covered in this leaflet, may be obtained from lubricants.technical@psopk.com