



CARIENT PLUS

Superior Performance You Can Feel



PSO Carient Plus is formulated with an appropriate viscosity grade to meet API SL/CF specifications. The oil is blended with high-quality refined base oils and an advanced additive package to provide improved high-temperature deposits control and lower oil consumption over the life of the oil for passenger cars and light commercial vehicles.

Benefits

- Extra engine cleanliness enhances service life of the engine parts.
- Superior protection against wear and tear at high temperatures.
- Suitable for extreme weather conditions.
- Improved high temperature oxidation control to give longer drain interval.
- Outstanding protection against rust and corrosion.
- Improved control of volatility and oil consumption.

Applications

- Recommended for all types of driving conditions and terrains where API SL/CF oil is applied.
- Formulated at SAE 20W-50 viscosity grade for gasoline engine cars best suited for the local environment.
- Oil may be used where API Service Category SJ and earlier categories are recommended.

Performance Standard

- API SL/CF

Typical Characteristics*

PROPERTIES	METHODS	TYPICAL RESULTS
		20W-50
Density @ 15°C, kg/L	ASTM D-4052	0.8967
K. Viscosity @ 100°C, cSt	ASTM D-445	19.78
K. Viscosity @ 40°C, cSt	ASTM D-445	178.5
Viscosity Index	ASTM D-2270	128
Flash Point (COC), °C	ASTM D-92	230
Pour Point, °C	ASTM D-97	-21
Total Base Number, mg KOH/g	ASTM D-2896	8

*These typical characteristics mentioned are based on current mean values.

Based on available information, this product does not contain any component that may produce any significant hazard to health when used for the recommended application. Guidelines for health and safety are available in Material Safety Data Sheet of the product. Dispose of used oil, containers, cartons labels in an environment friendly manner. Do not discharge used oil into drain, soil or water. Advice on application not covered in this leaflet, may be obtained from lubricants.technical@psopk.com