



# DIESELUBE HD

## Diesel Engine Oil

PSO Dieselube HD 50 is a high performance and high detergency lubricant especially developed to meet the stringent requirements of diesel engines where API CD/SE oil is recommended.

### Benefits

- Effective control of engine wear and deposits on engine parts.
- An economical product with good all-round performance.
- Protects against rust and corrosion.

### Applications

- Suitable for applications requiring performance level of API classification CD/SE.
- Appropriate choice for a wide variety of diesel engine vehicles for agricultural and off-road applications.
- Suitable to use in heavy and light commercial vehicles.

### Performance Standard

- API CD/SE

### Typical Characteristics\*

PROPERTIES	METHODS	TYPICAL RESULTS
		50
Density @ 15°C, kg/L	ASTM D-4052	0.9220
K. Viscosity @ 100°C, cSt	ASTM D-445	19.52
K. Viscosity @ 40°C, cSt	ASTM D-445	242.9
Viscosity Index	ASTM D-2270	92
Flash Point (COC), °C	ASTM D-92	234
Pour Point, °C	ASTM D-97	-6
Total Base Number, mg KOH/g	ASTM D-2896	10

\*These typical characteristics mentioned are based on current mean values.

Based on available information, this product does not contain any component that may produce any significant hazard to health when used for the recommended application. Guidelines for health and safety are available in Material Safety Data Sheet of the product. Dispose of used oil, containers, cartons labels in an environment friendly manner. Do not discharge used oil into drain, soil or water. Advice on application not covered in this leaflet, may be obtained from [lubricants.technical@psopk.com](mailto:lubricants.technical@psopk.com)