



## PRODUCT DESCRIPTION

PSO Flushing Oil is formulated with highly refined mineral base oil to flush engine after the old oil is taken out from the system and before the fresh oil is charged in.

## APPLICATION

- Suitable for flushing and cleaning of engine crankcase and other components prior to the application of the new oil in sump.

## BENEFITS

- Good characteristics for cleaning and flushing of engines/machine systems.
- Assists in drainage of contaminants thus giving protection to fresh charge.

## PRODUCT CHARACTERISTICS\*

PROPERTIES	METHOD	TYPICAL RESULTS
Kinematic Viscosity @ 40 °C, cSt	ASTM D-445	19.75
Kinematic Viscosity @100 °C, cSt	ASTM D-445	4.1
Viscosity Index	ASTM D-2270	95
Flash Point (COC), °C	ASTM D-92	180
Pour Point, °C	ASTM D-97	-6

\* These typical characteristics mentioned are based on current mean values.



### HEALTH & SAFETY

Guidelines for health, safety and handling are available in Material Safety Data Sheet of the product which can be obtained from PSO representative.



### ENVIRONMENT PROTECTION

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



### ADVICE

Advice on application not covered in this leaflet, may be obtained from PSO representative.